

Festoon Cable



Flat Cable

Part #	AWG Wire Size	# of Conds.	Ampacity @ 30°C Ambient	# of Strands	Insulation Thickness	Dimensions	Lbs/ft
FC1616	16	16	15	65	.030	.200" x 2.250"	.36
FC1612	16	12	15	65	.030	.200" x 1.605"	.27
FC1608	16	8	15	65	.030	.200" x 1.110"	.18
FC1412	14	12	17	41	.030	.210" x 1.700"	.34
FC1408	14	8	17	41	.030	.210" x 1.175"	.22
FC1404	14	4	25	41	.030	.210" x .625"	.12
FC1208	12	8	21	65	.030	.230" x 1.340"	.32
FC1204	12	4	30	65	.030	.230" x .710"	.16
FC1004	10	4	40	105	.030	.270" x .880"	.24
FC0804	8	4	50	168	.045	.365" x 1.190"	.42
FC0604	6	4	70	266	.060	.430" x 1.450"	.60
FC0404	4	4	90	420	.060	.490" x 1.690"	.75
FC0204	2	4	120	665	.060	.560" x 1.955"	1.27

*Other sizes available upon request

DESCRIPTION:

- Conductor of soft drawn bare copper
- Insulation of 105°C colour coded PVC
- Jacket compound PVC, -40°C to +105°C
- UV resistant
- CSA, UL & CE Listed
- FT1 and VW-1 Rated

APPLICATION:

For use with festoon systems for the conveyance of electrical power and control to cranes, hoists or any equipment which travels with a lateral traversing motion. Not recommended for severe flexing or impact at temperatures below -40°C.

Pendant Cable

Part #	AWG Wire Size	# of Conds.	# of Strands	Diameter	Lbs/ft
RPC1624	16	24	65/34	.745"	.37
RPC1620	16	20	65/34	.745"	.31
RPC1616	16	16	65/34	.605"	.25
RPC1612	16	12	65/34	.550"	.20
RPC1608	16	8	65/34	.465"	.14
RPC1604	16	4	65/34	.435"	.09
RPC1608PPS-4	16	8	65/34	.495"	.18
RPC1612PPS-4	16	12	65/34	.570"	.26
RPC1616PPS-4	16	16	65/34	.630"	.32
RPC1624PPS-4	16	24	65/34	.765"	.44

DESCRIPTION:

- Soft annealed bare copper per ASTM B3
- Insulation of 105°C colour coded PVC
- Resistance to UV, weather, oil and water
- CSA, UL & CE Listed

APPLICATION:

For use in festoon systems as vertical drop cable from a crane or hoist down to a pendant push button station.



5-375 Sheldon Dr. Cambridge, ON N1T 1B1

Tel: 1-888-822-2024 - Fax: 1-855-822-2022

E-mail: info@crane-controls.com - Web: www.crane-controls.com